







	DEV/ICIONI NIOTEC		UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES TOLERANCES AS FOLLOWS: 1 PLACE DECIMAL (.0): ±.030 2 PLACE DECIMAL (.00): ±.020 3 PLACE DECIMAL (.000): ±.010 ANGLES: ±2° SURFACE FINISH: 63RMS BREAK ALL EDGES: .010015 FILLETS & ROUINDS: R.015 - 0.30	DRAWN	NAME MH	DATE 06/25/2020	ULTRA PRESSURE COMPONENTS HOUSTON, TX			ſS
PROPRIETARY AND CONFIDENTIAL	REVISION NOTES AND DATES	AND DATES		CHECKED	KH	06/25/2020	TITLE:			
				DATE STARTED IN PRODUCTION:		9/16" Medium Pressure Plug 20,000 psi			~	
				06/25/2020						
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF			THREADS UNIFIED CLASS 2A - 2B CHAMFER THREADS 45° TO ROOT 30° CHAMFER IS OPTIONAL FOR MALE THREADS ONLY	ultra Pressum component we can handle			SIZE DWG. NO. R. 5406P-9M		Y	
ULTRA PRESSURE COMPONENTS IS PROHIBITED.						n handle Pressure	SCALE: 2:1	WEIGHT: 0.12	SHEET 1 (OF 1
5	^	4	3			2		'	1	

Ø.72