



SECTION A-A

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.

REVISION NOTES AND DATES

UNLESS OTHERWISE SPECIFIED:
 ALL DIMENSIONS ARE IN INCHES
 TOLERANCES AS FOLLOWS:
 1 PLACE DECIMAL (.0): ±.030
 2 PLACE DECIMAL (.00): ±.020
 3 PLACE DECIMAL (.000): ±.010
 ANGLES: ±2°
 SURFACE FINISH: 63RMS
 BREAK ALL EDGES: .010-.015
 FILLETS & ROUINDS: R.015 - 0.30
 THREADS UNIFIED CLASS 2A - 2B
 CHAMFER THREADS 45° TO ROOT
 30° CHAMFER IS OPTIONAL
 FOR MALE THREADS ONLY

	NAME	DATE
DRAWN	BM	01/14/2026
CHECKED	KH	01/14/2026
DATE STARTED IN PRODUCTION:		
01/14/2026		



ULTRA PRESSURE COMPONENTS HOUSTON, TX		
TITLE: 3/8" NPT Hollow Hex Plug 15,000 psi		
SIZE A	DWG. NO. 5406P-HH-6N	REV Y
SCALE: 2.5:1	WEIGHT: 0.03	SHEET 1 OF 1