



SECTION A-A

UNLESS OTHERWISE SPECIFIED:

- 1) DIMENSIONS ARE IN INCHES
- 2) TOLERANCES:
FRACTIONAL $\pm 1/64"$
ANGULAR: MACH $\pm 2^\circ$
ONE PLACE DECIMAL $\pm .020$
TWO PLACE DECIMAL $\pm .010$
THREE PLACE DECIMAL $\pm .005$
- 3) THREADS UNIFIED CLASS
2A - 2B
- 4) SURFACE FINISH 63 μ in Ra
- 5) CHAMFER THREADS:
MALE - 30° TO ROOT
FEMALE - 45° TO ROOT

| | NAME | DATE |
|---------|------|-----------|
| DRAWN | MH | 7/12/2017 |
| CHECKED | KH | 7/12/2017 |

DATE STARTED IN PRODUCTION:

7/12/2017



**ULTRA PRESSURE COMPONENTS
HOUSTON, TX**

TITLE:

HPC600 Nipple x 3/8" HP Male
30,000 psi

| SIZE | DWG. NO. | REV |
|----------|--------------|----------|
| A | HPC600-1-6HM | Y |

SCALE: 1.5:1 WEIGHT: 0.22 SHEET 1 OF 1

REVISION NOTES AND DATES

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.