







SECTION A-A

		UNLESS OTHERWISE SPECIFIED		NAME	DATE	ULTRA PR	ESSURE COMPONENTS		ſS
	REVISION NOTES AND DATES	ALL DIMENSIONS ARE IN INCHES TOLERANCES AS FOLLOWS: 1 PLACE DECIMAL (.0): ±.030 2 PLACE DECIMAL (.000): ±.020 3 PLACE DECIMAL (.000): ±.010 ANGLES: ±2° SURFACE FINISH: 63RMS	DRAWN	ВМ	10/03/2024	HOUSTON, TX			
			CHECKED	KH	10/03/2024	TITLE:			
			DATE ST.	DATE STARTED IN PRODUCTION:		UPC400 Nipple v 1/2" IIC M			ala
			10/03/2024		HPC600 Nipple x 1/2" JIC Male 15,000 psi				
PROPRIETARY AND CONFIDENTIAL		BREAK ALL EDGES: .010015 FILLETS & ROUINDS: R.015 - 0.30				10,000 psi			
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ULTRA PRESSURE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ULTRA PRESSURE COMPONENTS IS PROHIBITED.		THREADS UNIFIED CLASS 2A - 2B	ultraPressure		SIZE DWG. NO. REV				
		CHAMFER THREADS 45° TO ROOT 30° CHAMFER IS OPTIONAL			A HPC600-1-8JM Y			Υ	
		FOR MALE THREADS ONLY	GIG.	We can handle Pressure					
						SCALE: 1.5:1	WEIGHT: 0.19	SHEET 1 (OF 1
	†	_			_		ľ		

4 3 2